Serial No.: 10/019,326

Attorney Docket No.: 29462-032

IN THE SPECIFICATION

Please amend the paragraph beginning at page 1, line 10, as follows:

B 1

--EP-B1 0 334 410 has disclosed a nickel-ehrome chromium-molybdenum alloy that contains (by % of mass) the following alloy elements:

22.0 to 24.0 chrome chromium

15.0 to 16.5 molybdenum

Up up to 0.3 wolfram tungsten

Up up to 1.5 iron

Up up to 0.3 cobalt

Up up to 0.1 silicon

Up up to 0.5 manganese

up to 0.015 carbon

up to 0.4 vanadium

0.1 to 0.4 aluminum

0.001 to 0.4 magnesium

0.001 to 0.04 calcium--

Serial No.: 10/019,326 Attorney Docket No.: 29462-032

Please amend the paragraph beginning at page 2, line 3, as follows:

--EP B1 0 247 577 has disclosed an ally alloy on nickel basis containing ehrome chromium and molybdenum which can be hardened and containing, (in % by mass) the following alloy components:

Carbon max. 0.1

Manganese max. 5

Silicon max. 1

Phosphorus max. 0.03

Sulfur max. 0.03

Chrome Chromium 16[-] to 24

Molybdenum 7 to 12

Niobium 2 to 6

Titanium 0.50 to 2.5

Traces of aluminum up to 1

Boron max. 0.02

Zirconium max. 0.050

Cobalt max. 5

Copper max. 5

Serial No.: 10/019,326 Attorney Docket No.: 29462-032

and containing in addition at least 50% nickel as residue as well as impurities due to production, with the total of ehrome chromium and molybdenum no greater than 31 and the total of niobium, titanium and aluminum is such that their total atomic weight percentage comes to 3.5 to 5 and combines in solution annealed and hardened form a 0.2% stretch limit of over 100 ksi (690 MN/m²) combined with a resistance to fissure corrosion and crevice corrosion as well as against tension fissure corrosion in a chloride and sulfide environment at high temperature up to 260° C without requiring work below its recrystallization temperature.--

Please add a new paragraph after the third full paragraph at page 7 as follows:

--It is desirable to provide that an effective total WS =% Cr + 3[%Mo + 0.5 % W] + 16 % N \geq 54 is selected. It is also desirable that the stretch limit $R_{p0,2}$ of at least 400 N/mm² with the combination of WS \geq 54 with $R_{p0,2} \geq$ 400 N/mm² be selected in the solution-annealed state.--